



WORKARMA

TUFF RIG ULTRA RIGGERS GLOVE



Australian Standard
AS/NZS 2161.2:2020
AS/NZS 2161.3:2020
Lic.SMK41339
SAI Global



Premium Leather



Cut Resistant Grade F



Double Stitched



Durable

EN 388:2016



2533F

FEATURES

- Certified to AS/NZS 2161.2:2020 (ISO 21420) - General Requirements and Test Methods
- Certified to AS/NZS 2161.3:2020 (EN 388) - Protection Against Mechanical Risks
- Ultimate cut level F
- Aramid fibre lining and stitching
- Premium "A" grade cow leather
- Elastic wrist for improved fit
- Double stitching across wear seams offer strength
- Supple yet durable leather for increased comfort and durability
- Available in sizes S – 2XL

AVAILABLE RANGE

PART NUMBER	SIZE	PACK QTY
GRCFKFB0SMC	Small	1 Pair
GRCFKFB0MDC	Medium	1 Pair
GRCFKFB0LGC	Large	1 Pair
GRCFKFB0XLC	XL	1 Pair
GRCFKFB02XC	2XL	1 Pair

WORKARMA



TUFF RIG ULTRA RIGGERS GLOVE Hand Protection

TEST AND CERTIFICATION

Certified to

- AS/NZS 2161.2:2020 (ISO 21420) - General Requirements and Test Methods
- AS/NZS 2161.3:2020 (EN 388) - Protection Against Mechanical Risks

Certified by SAI Global



Australian Standard
AS/NZS 2161.2:2020
AS/NZS 2161.3:2020
Lic.SMK41339
SAI Global

EN 388:2016



2533F

TEST RESULT

STANDARD	TEST DESCRIPTION	CONFORMITY
EN 388:2016 +A1:2018	Abrasion resistance	Level 2
	Blade cut resistance	Level 5
	Tear resistance	Level 3
	Puncture resistance	Level 3
	Cut resistance TDM	Level F
EN ISO 21420:2020	pH	Pass
	Chromium VI	Pass
	Azo-dyes	Pass
	Dexterity	Level 5


UNDERSTANDING PROTECTION AGAINST MECHANICAL HAZARDS (EN 388:2016 +A1:2018)

Protection against mechanical hazards is symbolised by a pictogram followed by four numbers (performance levels) then two letters. For the first 4 positions the higher the number, the higher the level of protection. For the 5th position, the TDM cut test, A to F will be awarded for each gloves test result, with A being the lower score and F being the highest score. The letter P in the six position (if applicable) is for gloves certified to provide impact protection.

Example:

TEST	RATING RANGE	EXAMPLE RESULT
Abrasion	1-4	4
Cut (Coup Test)	1-5	x
Tear	1-4	4
Puncture	1-4	2
Cut (TDM Test ISO 13997)	A-F	C
Impact protection	P	P

EN 388:2016



4X42CP

For dulling during the cut resistance test, the coupe test results are only indicative, while the TDM cut resistance test is the reference performance result. If there is an X in any of the positions, it means this performance metric was not tested.

The above information should be used in conjunction with the wearers own risk assessment, adequate knowledge of AS/NZS standards.

APPLICATIONS

Including but not limited to industries such as:

- General handling
- Rail workers
- Construction
- Rigging
- Landscaping
- Demolition
- Mining
- Materials handling
- Construction

WORKARMA



TUFF RIG ULTRA RIGGERS GLOVE Hand Protection

FITTING INSTRUCTIONS

- Dry the hand before putting on the gloves
- Insert all five fingers into the cuff of the glove, and pull the cuff over your wrist until the glove is properly in place
- Check that the glove's fit is secure around the fingers and the palm. Also check the cuff, which should have a snug fit around your wrist
- If the fit feels too tight or too loose, consider changing size to avoid any tears or discomfort
- Remove glove by pulling on fingers and slide glove over hand

WARNINGS AND LIMITATIONS OF USE

- Wearer must complete a risk assessment to determine suitable protection required
- The selection of the right glove must be made according to the specific needs of the workplace, the type of risk and its environmental conditions
- Check that the glove does not present holes, cracks, tears, colour change etc and discard any glove presenting such defects
- Replace gloves when glove shows signs of wear and tear
- Gloves shall not be worn when there is a risk of entanglement by moving parts of machines
- The tested performance levels only refer to the palm side of the glove

STORAGE, SHELF LIFE AND CLEANING

- Store in a dry environment with temperatures between -5°C and +50°C
- Sunlight may cause gloves to become discoloured and lose their dexterity. Store away from direct sunlight
- It is not recommended to machine wash or hand wash with water
- If cleaning is required, use a specialised leather cleaner

WORKARMA

Bremick Pty Ltd

Head Office | 88 Dalmeny Avenue, Rosebery 2018
National Distribution Centre | M5/M7 Logistics Park,
Warehouse 4B, 290 Kurrajong Road, Prestons NSW 2170

www.workarma.com.au

www.bremick.com.au